



**MCP**  
FIXED PULVERIZER




# MCP

## FIXED PULVERIZER

The MCP design enhances simplicity and performances. It is engineered for secondary demolition on the ground and is available for a wide range of construction machines weighting from 2 to 38 ton.

• The **reinforced MCP structure** is designed to last forever and makes the tool extremely functional to operate on the ground. In addition, it facilitates the crushed material drop off **increasing efficiency**.

• The **Speed-Valve** reduces opening and closing time boosting productivity. Not available for MCP300 and MCP480 models.



• The interchangeable parts, like teeth plates and blades, ensure **quick and easy maintenance**.



## TECHNICAL DATA

BT.MCPmini.06

BT.MCP.06

MODEL		MCP300	MCP480	MCP800	MCP910
EXCAVATOR WEIGHT	t	2-4	5-10	18-27	28-38
TOOL WEIGHT *	kg	150	490	2050	2850
OPENING	mm	300	480	850	1000
HEIGHT	mm	770	1225	2070	2400
HYDRAULIC WORKING PRESSURE	bar	200-250	220-280	280-320	280-320
OIL FLOW	l/min	30-60	80-100	180-220	220-280

We are constantly improving our products and therefore we reserve the right to change the design and technical specifications without prior notice.  
\* Tool weight does include Mantovanibenne top bracket.

RIF. 97877/E.12/18 REV.02

