



RP

ROTATING PULVERIZER



RP

ROTATING PULVERIZER

The essential features for demolition jobs in a single tool. The RP is suitable for primary and secondary demolition, and it is available for 7 to 35 tons excavators.

- The **reinforced RP structure** is designed to last forever and facilitates the crushed material drop off increasing efficiency.
- The continuous **hydraulic rotation** enables accurate tool positioning in every working environment. In addition, the double-row thrust bearing ensures **high robustness and increases safety**.
- The **Speed-Valve** reduces opening and closing time boosting productivity.
- The **rod-cutting blades** are interchangeable and can be turned four times before replacement.



TECHNICAL DATA

BT.RP.08

REF. 97872/E 12/18 REV.02

MODEL		RP07	RP16	RP18	RP25
ROTATION		360° Hydraulic			
EXCAVATOR WEIGHT	t	7-10	16-20	21-26	27-35
TOOL WEIGHT*	kg	660	1720	2000	2750
OPENING	mm	500	700	760	930
HEIGHT MAX.	mm	1560	2020	2136	2440
HYDRAULIC WORKING PRESSURE	bar	220-280	300-350	300-350	300-350
OIL FLOW	l/min	90-120	180-200	180-200	200-220

We are constantly improving our products and therefore we reserve the right to change the design and technical specifications without prior notice.

* Tool weight does include Mantovanibenne top bracket.

